

OFFICE OF THE CHIEF DISTRICT MEDICAL & PUBLIC HEALTH OFFICER

GAJAPATI, PARALAKHEMUNDI

Phone No.06815-222205/ 224081

Email: centralstoregajapati@gmail.com

Letter No.**3644/Substore/2018-19**

Dated.**10.05.2018**

Tender Call Notice

Bid Reference No. – CDM & PHO (Gajapati) – 2018-19 – DWH/MCH – 01

Sealed Tenders are invited from registered manufacturers/ authorized distributors/ suppliers for supply of Equipment, Instrument & furnitures for Gajapati District. The intended suppliers, manufacturer, Distributors are required to quote the rates for the following items. The tender reaching after due date shall summarily be rejected. The specification and names of the items of the manufacturing company should be mentioned in the price bid. The equipments/ items are to be supplied with door delivery & installed within 30days of receipt of the orders and should submit the installation certificate and warranty certificate. The last date of submission is **Dt.05.06.2018 by 1.00 PM** through **Reg. Post /Speed Post or Courier** services only along with all the relevant documents. The Bidders should specifically super scribe, "**TENDER CALL NOTICE FOR SUPPLY OF EQUIPMENT, INSTRUMENT & FURNITURES FOR GAJAPATI DISTRICT**" on the top left corner of the outer envelope containing Bid reference number. The Bidders may download the Tender Documents directly from the WEBSITE available at www.gajapati.nic.in within **Dt.05.06.2018**. The Tenders received shall be opened at **10.00 AM on Dt.06.06.2018** in the chamber of CDM & PHO, Gajapati and the said firms are requested to attend on the said date and time or send their representative. The undersigned reserves the right to reject or cancel any or all the tenderers without assigning any reason thereof.

Yours Sincerely,


CDM & PHO, Gajapati

ITEMS TO BE PROCURED FOR THE YEAR 2018-19

Sl. No	Name of the Item	Specification	Remarks
ITEMS FOR DISTRICT DRUG WAREHOUSE			
1	Cold Box & Ice pack		
2	Thermo hygrometer		
3	Air Conditioner	1T/ 1.5 T/ 2T	
4	Stabilizer for AC		
5	Aquaguard/ Water Purifier		
6	Aluminium ladder		
7	ABC Powder Fire Extinguisher (4 kg)		
ITEMS FOR MCH BUILDING			
8	Desktop Computer	Intel i3 7 th Gen	
9	UPS		
10	Laser Printer (Print, Scan, Copy)		
11	Flatbed Scanner		
12	Heavy Duty Scanner		
13	LED TV		
14	LCD Projector		
15	Projector Screen		
16	White/colour boards		
17	DVD Player		
18	Photo Copier		
19	Laptop	Intel i5 7 th Gen	
20	External Hard disk		
21	Refrigerator		
22	Refrigerator(double door)		
23	Washing machine with drier		
24	Vacuum cleaner		
25	Camera (35mm, digital with colour printer)		
26	Racks (Steel)		
27	Doctor's Table		
28	Duty Table for Nurses		
29	Steel Cup-board		
30	Patients Waiting Chairs (Moulded)*		
31	Filing Cabinets (for records)*		
32	Stores Almirah		
33	Torch		
34	Doctor's Chair	Full Back	
35	Office Chairs/ Executive Chair	Medium Back	
36	Office Table		
37	Chair (Meeting hall Purpose)		
38	Bedspreads		
39	Blankets Red and blue		
40	Table cloth		

41	Doctor's overcoat		
42	Hospital worker OT coat		
43	Patients house coat (for female)		
44	Patients Pyjama (for male) Shirt		
45	Abdominal sheets for OT		
46	Pereneal sheets for OT		
47	Leggings/ SNCU Staff Dress		
48	Mats (Nylon)		
49	Mosquito Net		
ITEMS FOR BMWM			
50	Stainless Steel Pole Hanging Dustbin	50 ltrs	
51	Foot Operated Yellow colour dustbin stand	Iron/Stainless steel with bio hazard symbol(Odisha Govt. Supply) 30 ltrs	
52	Foot Operated Red colour dustbin stand	Iron/Stainless steel with bio hazard symbol(Odisha Govt. Supply) 30 ltrs	
53	Foot Operated Black colour dustbin stand	Iron/Stainless steel with bio hazard symbol(Odisha Govt. Supply) 30 ltrs	
54	Foot Operated Blue colour dustbin stand	Iron/Stainless steel with bio hazard symbol(Odisha Govt. Supply) 30 ltrs	
55	Wheel barrow		
56	Green Colour Waste Bin HDPE material	Swing model 30ltrs	
57	Food trolley		
58	Eureka Forbes 3 bucket mopping trolley		

Terms and Conditions:-

- The bidder is free to quote for single category or all categories of appliances individually. However, the contract shall be for the full quantity for a particular item.
- All duties, taxes and other levies payable including the supply at our place by the vendor under the contract shall be included in the total price.
- Rates quoted should also include installation of material at our site.
- The items for which quotations have been submitted must be in accordance with the specifications given. Variations in specifications (if any) should be mentioned in a separate letter.
- The rates quoted by the bidder shall be fixed for the duration of the contract and shall not be subject to adjustment on any account.
- The bidder should submit the separate price bid/ financial quotation.

- Period of delivery- The items are to be delivered within a maximum time limit of 30 days from the issue of Purchase order.
- The tender shall be submitted in two parts viz, (a) Technical Bid and (b) Financial Bid and both the parts are put in a single envelope.
- Technical bid shall consist of technical details, and should be submitted in duplicate. Deviations (if any) from tender specifications and commercial terms and conditions should be clearly mentioned. The tender form shall be submitted with this bid duly signed by the bidder.
- Financial bid shall consist of price details
- The tender is liable to be rejected if complete information is not given therein or if the particulars and date (if any) asked for in the schedule tender are not fully filled in. Particular attention must be paid to delivery date and also to the particulars referred to in the condition of the contract. The tenderer should sign every page.
- The technical bids should be submitted in sealed covers, marked "Technical Bid for procurement of Equipment"
- Only technically qualified bidder's financial bids shall be open.
- Tenders not complying with the above conditions are liable to be rejected at the sole discretion of CDM & PHO, Gajapati without any further reference.
- This tender is not transferable.

PRE-QUALIFICATION:

Manufacturing units /Authorised dealers/Traders are eligible to participate in the tender provided, they have

- This Tender document can be downloaded from website www.gajapati.nic.in. The filled in/complete in all respect tender document must be submitted with tender document fee of Rs. 500 /- (Non refundable) in the form of Demand Draft in favour of the **ZSS NON-NRHM FUNDS, GAJAPATI** payable at SBI Main Branch, Paralakhemundi.
- **EMD:** As indicated in the Tender Notice Rs. 10000 /- only in form of Demand Draft in favour of the "**ZSS NON-NRHM FUNDS, GAJAPATI** payable at SBI Main Branch, Paralakhemundi" is refundable.
- **The bidder/ company offices must have been registered in Odisha.**
- Copy of Certificate **ISO 9001:2008 or ISO 9001:2015** must be submitted.
- The intended suppliers should also furnish along with the quotations the latest **GST Certificate, GST monthly return for last applicable month Certificate, PAN Card**. The authorised distributor/trader should submit the **Manufactures Original Authorization Certificate** from the competent authority for this particular tender. If not, the Authorised distributor/Traders are not eligible to participate in the tender. **Colour Xerox copies of authorization certificate are not acceptable in any condition**. If so, the Authorised bidder/distributor/Traders are not eligible to participate in the tender.

- Bidders who have been blacklisted either by the Tender inviting authority or by any district/state Govt. or Central Govt. organization for the quoted item is not eligible to participate in the tender during the period of blacklisting. **Affidavit** of the same to be submitted stating that the firm has **neither been black listed nor any criminal cases** pending against them.
- The bidder should have presence in Odisha with support Centers. The bidder should have technical manpower with experience to provide service. A Self Certified letter by an authorized signatory; OR Undertaking for setting up Service Support Centres through Channel partner and deployment of Resident Engineers.
- **Copy of original Tender book and schedules, duly signed by manufactures/bidders.**
- **General:** CDM & PHO, Gajapati reserves the right to choose, accept or reject any or all requests/offers, in full or part and also reserve the right at any stage to reduce or increase the quantity and split the order.

Evaluation of Quotations

CDM & PHO, Gajapati will evaluate and compare the quotations determined to substantially responsive i.e. which are properly signed; and confirm to the terms and conditions, and specifications.

The evaluation will be done based on the following parameters:

- **Price quote**
- **Quality & Guarantee offered by the vendor**

Award of Contract

The purchaser will award the contract to the bidder whose quotation has been determined to be substantially responsive and who has offered the lowest evaluated quotation price.

Notwithstanding the above, CDM & PHO, Gajapati reserves the right to accept or reject any quotation and to cancel the bidding process and reject all quotations at any time prior to the award of contract without giving any reason.

The bidder whose bid is accepted will be notified of the award of contract by the purchaser prior to expiration of the quotation validity period. The terms of the accepted offer shall be incorporated in the purchase order.

	±0.5°C at 25°C
Display	dual LCD with 4.5 positions
Battery	9V battery (PP3)
Response time % r.h.	about 10 sec. (90 % @ 25° C air temp.)
Dimensions	225 x 45 x 34mm
Weight	200g

SPLIT AIR CONDITIONER & STABILIZER

Specifications:

Specifications for supply, installation, testing and commissioning of eco friendly split air conditioner.

TECHNICAL SPECIFICATION

AIR CONDITIONER 1Tonne

1	Star rating : 5 Star 2017 model/ 3 Star 2018 model
2	Cooling Capacity(KW/hr): above 3000KW/hr
3	Compressor Type: Rotary type
4	Compressor warranty: 5years
5	Air circulation(CFM H/M/L): above 300/250/200
6	Moisture Removal(L/hr): above 1
7	IDU Noise level(dBA) ≤ 45/40/35
8	Control : Microprocessor controlled codeless remote
9	Power Source (V/Hz/Ø) : 230/50/1
10	Display : LED/LCD
11	Remote control distance : Min 10 meters
	Voltage Stabilizer
12	Voltage Stabilizer Wall mount type with Time delay,High& low voltage& Thermal overload protection.
13	Capacity: 4 KVA
14	Warranty: 2 years
15	Input voltage: 130-300 V
16	Output Voltage : 200-240 V
17	High Voltage Cut Off : 240
18	Efficiency: >95%
19	Frequency : 50Hz
	Equipment shall be supplied along with :
20	4 mtr copper piping with superlon insulation for suction line
21	4 mtr copper piping with superlon insulation for Discharge line
22	1 mtr PVC piping for drain
23	Indoor - Outdoor unit connecting power cable and required cable from power socket to stabilizer and from stabilizer to AC Unit
24	Base plate for hanging indoor unit

TECHNICAL SPECIFICATION

AIR CONDITIONER 1.5T

1	Star rating : 5 Star 2017 model/ 3 Star 2018 model
2	Cooling Capacity(KW/hr): above 3000KW/hr
3	Compressor Type: Rotary type
4	Compressor warranty: 5years
5	Air circulation(CFM H/M/L): above 450/350/300
6	Miosture Removal(L/hr): above 1.5
7	IDU Noise level(dBA) \leq 55/50/45
8	Control : Microprocessor controlled codeless remote
9	Power Source (V/Hz/ \emptyset) : 230/50/1
10	Display : LED/LCD
11	Remote control distance : Min 10 meters
	Voltage Stabilizer
12	Voltage Stabilizer Wall mount type with Time delay, High& low voltage& Thermal overload protection.
13	Capacity: 4 KVA
14	Warranty: 2 years
15	Input voltage: 130-300 V
16	Output Voltage : 200-240 V
17	High Voltage Cut Off : 240
18	Efficiency: >95%
19	Frequency : 50Hz
	Equipment shall be supplied along with :
20	4 mtr copper piping with superlon insulation for suction line
21	4 mtr copper piping with superlon insulation for Discharge line
22	1 mtr PVC piping for drain
23	Indoor - Outdoor unit connecting power cable and required cable from power socket to stabilizer and from stabilizer to AC Unit
24	Base plate for hanging indoor unit

TECHNICAL SPECIFICATION

AIR CONDITIONER 2T

1	Star rating : 3 Star/4 Star/5 Star
2	Cooling Capacity(KW/hr): above 3000KW/hr
3	Compressor Type: Rotary type / Scroll Type
4	Compressor warranty: 5years
5	Air circulation(CFM H/M/L): above 500/450/350
6	Miosture Removal(L/hr): above 1.8
7	IDU Noise level(dBA) \leq 55/50/45
8	Control : Microprocessor controlled codeless remote
9	Power Source (V/Hz/ \emptyset) : 230/50/1
10	Display : LED/LCD
11	Remote control distance : Min 10 meters
	Voltage Stabilizer
12	Voltage Stabilizer Wall mount type with Time delay, High& low voltage& Thermal overload protection.
13	Capacity: 4 KVA
14	Warranty: 2 years
15	Input voltage: 130-300 V
16	Output Voltage : 200-240 V
17	High Voltage Cut Off : 240

18	Efficiency: >95%
19	Frequency : 50Hz
	Equipment shall be supplied along with :
20	4 mtr copper piping with superlon insulation for suction line
21	4 mtr copper piping with superlon insulation for Discharge line
22	1 mtr PVC piping for drain
23	Indoor - Outdoor unit connecting power cable and required cable from power socket to stabilizer and from stabilizer to AC Unit
24	Base plate for hanging indoor unit

Terms and conditions:

- Eco friendly gas R410a or equivalent should be used as a refrigerant. The refrigerant gas should not have any action in Ozone layer depletion.
- The eco friendly split air conditioner should be energy efficient.
- Department will not be provided any wire or cable for the installation of same. The outdoor and indoor units power supply cable should be provided with single length cable, as no joints are permitted.
- Only Copper material condenser units and cooling unit will be accepted.
- Minimum 4.00 mtrs Copper tubes along with each unit must be supplied.
- In order to cover the blank area, as per site requirement supplier should provide glasses (5mm) and sun films, MS grills or Aluminum grills..
- Parties should have to complete all finishing works like pocket filling, wall colour works or any other civil works from inside and out side of building before submission of final bill.
- No water leakage should occur after repair works completed by the supplier, at least for one rainy season.
- Only branded make units will be accepted.

AQUAGUARD SPECIFICATION

Water Purifier (UV)

Features:	Auto Shut Off, Complete 4 Stage Purification System, Environment Protection, Intelligent Purity Sensor System, Mineral Guard Plus, Unique E Boiling Plus, Voltage Stabilizer
Installation:	Chemi block, Clarity Cartridge, Mineral Guard, UV chamber
(WxDxH):	355x102x307
Weight:	5kg
Operating Voltage:	230V 24V
Warranty:	1 Year(s)
Purification Technology:	UV
Storage Capacity:	6 Litre(s)
Flow Rate:	1
Type of Water Purifier:	Direct Flow

Water Purifier (RO+UV)

Features:	Advanced Mineral Guard Technology, Advanced RO+UV Technology, Complete protection, MTDS Regulator, Smart Auto fill, Unique e-boiling plus
No of Purification stages:	8
Installation:	Wall Mounted
Membrane Type:	Thin Flim Composite RO
(WxDxH):	369x235x498
Weight:	7 kg
Operating Voltage:	230V 24V
Warranty:	1 Year(s)
Applicable TDS Range in Input Water:	1- 2000 mg/litre
Recommended for:	Universal
Power Consumption:	45 Watts
Ultraviolet Lamp:	11 watts
Life of UV Lamp:	8000 burning hours
Input Water Pressure (max):	2.0 kg/sq.cm
Input Water Pressure (min):	0.6 kg/sq.cm
Input Water Temperature:	10°C - 40°C
Input Water Chlorine:	0.2 mg/litre
Input Water Iron:	0.3 mg/ litre
Input Water Turbidity:	15 NTU
Purification Technology:	RO+UV
Storage Capacity:	8.5 Litre(s)
Flow Rate:	15 Ltr/ hour
Type of Water Purifier:	Storage

ALUMINIUM HEAVY DUTY LADDER

Step Ladder(8 or 10 Step Heavy Weight)

- Opening Size: 186.69 x 35.56 x 119.38 cm/Closing Size: 35.56 x 199.39 cm/Platform Dimension: 25.4 x 25.4 cm/ Platform Height: 148.59 cm/Step Jump: 22.86 cm
- Capacity is 150 kg / 330 lbs Heavy Duty Aluminium ladder for extra durability with a weight bearing capacity up to 150 kg, High quality aluminum and MUST have for every Home or Commercial Space.
- Non-skid ribbed steps knee guard for added support Edge protector/saree guard anti-skid PVC shoes
- Ideal for every house hold, office, warehouse, godown or shop. Corrosion resistant structure for longer life. Wide base design for firm, comfortable and safe climb.

Simple Aluminium Ladder (8 or 10 Step)

- Material of Frame: High quality aluminium
- Surface Finish: oxidation
- Thickness: 1.2mm
- Max Load: 150kg
- High quality aluminum and MUST have for every Home or Commercial Space.
- Non-skid ribbed steps knee guard for added support Edge protector/saree guard anti-skid PVC shoes
- Ideal for every house hold, office, warehouse, godown or shop. Corrosion resistant structure for longer life. Wide base design for firm, comfortable and safe climb.

Sample:-



Step Ladder



Simple sliding Ladder

Specification of Desktop Computer, UPS & Laser Printer

Item Name	Category	Description
Desktop Computer	Processor	Intel i3 7th Generation processor / equivalent AMD processor with minimum 2 core, 2.10 GHz frequency or higher and 6 MB Cache or higher
	Chipset	Q series Chipset Motherboard or Equivalent Chipset Motherboard
	Graphics	Integrated HD Graphics or Dedicated HD Graphics Card
	Memory	4GB DDR4 2133 MHz or higher RAM expandable to 16 GB
	Hard Disk Drive	1 TB 7200 RPM SATA Hard Drive or higher
	Monitor	18.5" or higher LED Monitor with Non Touch Display Type
	Display Resolution	1366 X 768 Pixel or Higher
	Ports	1. 1 X VGA 2. 1 X HDMI/ Display Port 3. 2 X USB 3.0 4. 4 X USB 2.0 5. 1 X RJ 45 6. 1 X Headphone with Microphone Jack
	Ethernet	Integrated Gigabit Ethernet 10/100/1000
	IPv6 compliance	System should be IPv6 Ready
	Expansion Slot	PCIeX1, PCIeX16
	Keyboard & Mouse	OEM Keyboard & OEM optical scroll mouse with USB interface
	Audio	Integrated HD Audio
	Optical Drive	Integrated DVD RW 8X or above
	Operating	Pre-loaded Windows 10 Standard Edition with License & recovery CD from Direct Named Account of Microsoft with Certificate of Authenticity having OEM name
	System	(64-bit)
	MS Office	Pre-loaded MS office Standard 2016 Single OLP C (64 bit)
	Anti-Virus	Antivirus with Antimalware and Internet security with 3 years Subscription.
	Power Supply	230 V, 50 Hz
	Certification	ISO 9001:2015, Energy Star 6.1/ TCO, ISO 14001:2015, Windows, RoHS Compliant
	IDC Ranking	OEM should be ranked within Top 5 as per IDC report for Desktop in India for any quarter of 2017, Letter/Report from IDC should be attached along with the bid
	Data Protection	Data Protection System Protection Tool
Management Software	Management Software OEM's own Management Software (preloaded)	
I/O Ports Static Protection	Electrostatic Discharge protection	
Warranty	3 Years Onsite OEM warranty (OEM undertaking on letter head need to be submitted along with bid)	

1 KVA UPS for Computer	<p>The 1 KVA off line UPS for computer should have following Specification.</p> <ul style="list-style-type: none"> ➤ Watts: 500w ➤ Battery Alarms: Audible & LED ➤ Input Voltage: +/- 20% of nominal ➤ Output Voltage: -10% to +6% of nominal ➤ Frequency: 50/60 Hz of nominal ➤ Runtime at 100% load: 15 minutes ➤ Communication: USB/Serial ➤ Warranty: 2 years on site comprehensive warranty & support 																													
Laser Printer (multifunction) (print, scan, copy)	<table border="1"> <tr><td>Function</td><td>Printer, Copy and Scan</td></tr> <tr><td>First Page Out (Ready)</td><td>Less than or equal to 10 Sec</td></tr> <tr><td>Duty Cycle</td><td>More than 25000 pages/ month</td></tr> <tr><td>Print Technology</td><td>Laser</td></tr> <tr><td>Duplex Printing</td><td>Automatic</td></tr> <tr><td>Output Type</td><td>Mono Chrome</td></tr> <tr><td>Printer Speed</td><td>25 ppm or higher</td></tr> <tr><td>Paper Size</td><td>Legal, A4, LTR, A5, A6, B5, B6, custom, executive</td></tr> <tr><td>Print Resolution</td><td>1200*1200 dpi</td></tr> <tr><td>Interfaces/ Connectivity</td><td>Ethernet, USB 2.0</td></tr> <tr><td>Memory</td><td>128 MB or higher</td></tr> <tr><td>Supported environment</td><td>Windows 7/8 (32 bit/64 bit), Mac OS</td></tr> <tr><td>Scan Resolution, Optical</td><td>Up to 1200x1200 dpi (mono/colorflatbed)</td></tr> <tr><td>Warranty</td><td>Minimum Three (3) years on-site comprehensive warranty and support</td></tr> </table>	Function	Printer, Copy and Scan	First Page Out (Ready)	Less than or equal to 10 Sec	Duty Cycle	More than 25000 pages/ month	Print Technology	Laser	Duplex Printing	Automatic	Output Type	Mono Chrome	Printer Speed	25 ppm or higher	Paper Size	Legal, A4, LTR, A5, A6, B5, B6, custom, executive	Print Resolution	1200*1200 dpi	Interfaces/ Connectivity	Ethernet, USB 2.0	Memory	128 MB or higher	Supported environment	Windows 7/8 (32 bit/64 bit), Mac OS	Scan Resolution, Optical	Up to 1200x1200 dpi (mono/colorflatbed)	Warranty	Minimum Three (3) years on-site comprehensive warranty and support	
Function	Printer, Copy and Scan																													
First Page Out (Ready)	Less than or equal to 10 Sec																													
Duty Cycle	More than 25000 pages/ month																													
Print Technology	Laser																													
Duplex Printing	Automatic																													
Output Type	Mono Chrome																													
Printer Speed	25 ppm or higher																													
Paper Size	Legal, A4, LTR, A5, A6, B5, B6, custom, executive																													
Print Resolution	1200*1200 dpi																													
Interfaces/ Connectivity	Ethernet, USB 2.0																													
Memory	128 MB or higher																													
Supported environment	Windows 7/8 (32 bit/64 bit), Mac OS																													
Scan Resolution, Optical	Up to 1200x1200 dpi (mono/colorflatbed)																													
Warranty	Minimum Three (3) years on-site comprehensive warranty and support																													

DOUBLE DOOR REFRIGERATOR SPECIFICATIONS

Item Name	Category	Description
Double Door Refrigerator	Energy Rating	Inverter Compressor Star
	Other Features	Water Dispenser, Ice Dispenser
	Type	Double Door
	Capacity	250 Litres or more
	Air Circulation	Yes
	Refrigerator Type	Double Door
	Energy Rating	Inverter Compressor Star
	Defrosting Technology	Frost Free
	Operation Control	Yes
	Super Cool Function	Yes
	Refrigerant	R-600A
	Ice Tray	2
	Capacity Freezer	69
	Freezer Location	Top
	Icemaker Type	Ice MAX
	No Of Shelves freezer	2
	Freezer Lamp	Yes
	Door Basket	Yes
	Chiller Tray	Yes
	Drawers	Yes
Gasket Type	Removable	
Vegetable Basket	Yes	
Egg Cum Ice Tray	Yes	

Vegetable Crispers	Yes
Chiller	Yes
No Of Doors	4
No Of Shelves	2
Egg Tray	Yes
Convertible Veg Box	Yes
Ice Dispenser	Yes
Interiors Lamp	LED
Color	-----
Exterior Door Finishing	Glossy Finish
Water Dispenser	Yes
Handle	Metallic Bar
Humidity Controller	Yes
Moist Balance Crisper	Yes
Deodorizer	Yes
Child Lock	Yes
Depth	688 mm
Width	555 mm
Height	1545 mm
Compressor Warranty	5 Years
Warranty	1 Year
Package Contents	Main Unit, Power Cord Attachments, User Manual & warranty Card

SINGLE DOOR REFRIGERATOR SPECIFICATIONS

Item Name	Category	Description
Single Door Refrigerator	Energy Rating	4/5 Star
	Other Features	Power cut technology, Deodorizer
	Type	Single Door
	Capacity	215 Litres or more
	Cooling Technology	Direct Cool
	Ice Tray	Twisted
	Freezer Features	Ice Cube Tray
	Power Supply	135-290 volts
	Shelves	2/3
	Color	----
	Exterior	Chrome Handle Bar
	Door Alarm	No
	Door Lock	Yes
	Additional Features	Stabiliser Free Operation, Fresh tech Kit
	Installation Type	Free-Standing
	Batteries Required	No
	cool wave	Minimum 9 hours
	stabilizer free operation	Yes
	Depth	636 mm
	Width	549 mm
	Height	1308 mm
	Compressor Warranty	10 years
	Warranty	Compressor, Body, 1 years, 1 Year comprehensive, 5 Years on compressor
Package Contents	Main Unit, User Manual, Warranty Card	

WASHING MACHINE WITH DRYER SPECIFICATIONS

Item Name	Category	Description
Washing Machine With Dryer	Washing Features	Fully Automatic
	Drying	Child Lock
	Additional Features/ Type	Dryer
	Key Features	5.5 KG or 6.00 kg
	Timer	Yes
	Control	Fully Automatic
	Energy Consumption Kwh	2.9
	Frequency	50 Hz
	Voltage	220 Volt
	No Of Wash Cycles	2
	Technology	Fully-automatic
	Rinse	Yes
	Warranty	4 Years
	Delivery Installation	Yes
	Safety Door Switch	Single Pole micro Switch
	Display	LED Display
	Weight	Minimum 26 Kg or more
	Spin	Yes
	Interior	Stainless Steel
	Intensive Wash	No
	Synthetic	Yes
	Quick	No
	Cotton	Yes
	Pre Wash	No
	Mixed Fabric	Yes
	Control System	Electro mechanical
	Lint Collector	Yes
	Child Lock	Yes
	Additional Features	Anti-Crease, Germ Free Clothes, Wall & Machine Mountable, Terminal Overload Switch, Cool Down Time : 13 mins, Maximum Cycle Time : 180 mins, Motor Rating : 125 watts, Air Out Flow Adjustable : 2 Way - Top and Side
	Depth	600 mm
	Width	530 mm
	Height	720 mm
Installation Type	Free-Standing	
Batteries Included	No	
Batteries Required	No	
Included Components	Washing Machine, Hose Drain, Hose Inlet, Warranty Card, User Manual, Shutter (Rat Mesh), Clip Ring, Screw Fitting	

VACUUM CLEANER

- Powerful suction and blower function
- Dual functions for collecting dry dust and wet spills
- Wide range of accessories to suit varied cleaning needs
- Specially designed 360 degree swivel wheels for easy movement
- Larger capacity of plastic container for water-8 litres and dust-10 litres collection
- Automatic cord winder for convenience
- Convenient 8 meter radius of operation
- Blower efficiency: 650 litres/min
- Warranty: 1 year on product
- Power: 1150 watts
- Multi-purpose Brush, Crevice Nozzle, Upholstery Brush, Carpet / Floor Brush are place inside the storage tank
- Warranty: 1 year on product
- Includes: Carpet / Floor Brush, Multi-purpose Brush, Wet Squeeze, 2 Extension Tubes, 1 Unit, User Manual, Upholstery Brush, Flexible Hose Pipe, Warranty Card, Crevice Nozzle

FILING CABINET

Sample:-



STEEL RACK

Sample:-



OFFICE CHAIR/ EXECUTIVE CHAIR/ DOCTORS CHAIR

Full Back Executive Chair :-

Sample:-



The unit intended for use in various location of the Emergency Department to use as waiting area chairs.

- The unit shall have aluminium base with castors.
- The unit should have synchro mechanism with armrest.
- The unit should have seat in PVC Upholstery
- The unit should be in black colour
- The size of unit shall be approximately 600mm in diameters
- The unit shall come with an armrest.
- The frame structure shall be constructed with durable steel able to resist to rust. All joints shall be welded and all exposed surfaces shall be straight and true to line and curve. The entire structure shall be coated with a layer of anti-corrosion paint follow by another 2 finishing coats either power coating or nylon polyester coating to withstand periodic cleaning and typical abuse.
- The unit should be heavy duty.
- The unit also must be sturdy and would not sink once sit upon.

- Chair Diameter: 600mm
- Chair shall have five (5) legged chair base.
- The backrest should conform to the natural curvature of your spine, and provide adequate lumbar support.
- The safe loading capacity of the seat shall be approximately about 100 kg excluding the weight of unit itself.
- The safe loading capacity of the back rest shall be approximately about 30 kg excluding the weight of unit itself.
- The standard accessories shall include the following items and other items necessary required for normal operation and usages of the trolley.

All accessories shall be deemed as included in the tender base price.

 - a) Seat with PVC Black upholstery.
 - b) Come with adjustable armrest.
 - c) Five (5) legged aluminium base.

Medium Back Executive Chair :-

Sample:-



The unit intended for use in various location of the Emergency Department to use as waiting area chairs.

- The unit shall have aluminium base with castors.
- The unit should have synchro mechanism without armrest.
- The unit should have seat in PVC Upholstery
- The unit should be in black colour.
- The size of unit shall be approximately 600mm in diameters
- The unit shall come with an armrest.
- The frame structure shall be constructed with durable steel able to resist to rust. All joints shall be welded and all exposed surfaces shall be straight and true to line and curve. The entire structure shall be coated with a layer of anti-corrosion paint follow by another 2 finishing coats either power coating or nylon polyester coating to withstand periodic cleaning and typical abuse.
- The unit should be heavy duty.
- The unit also must be sturdy and would not sink once sit upon.
- The backrest should conform to the natural curvature of your spine, and provide adequate lumbar support.
- The safe loading capacity of the seat shall be approximately about 100 kg excluding the weight of unit itself.
- The safe loading capacity of the back rest shall be approximately about 30 kg excluding the weight of unit itself.

- The standard accessories shall include the following items and other items necessary required for normal operation and usages of the trolley.
All accessories shall be deemed as included in the tender base price.
 - a) Seat with PVC Black upholstery.
 - b) Come with adjustable armrest.
 - c) Five (5) legged aluminium base.

Optional Accessories

All optional accessories or consumables that are optional shall be listed separately with unit prices clearly indicated.

OFFICE TABLE

Size: L (48”) X B (24”) X H (30”

Structure 25mm thick medium density fiber/ particle board faced with 0.8 mm thick laminate and all the exposed edges provided with machine pressed 0.8mm thick PVC edge bands glued with hot melt EVA glue. All the panels are inter connected and attached to top with rastex, dowel and sockets (of Hettich make). All the exposed edges of under structure provided with machine pressed 0.8mm thick PVC edge bands glued with hot melt EVA glue.



DUTY TABLE FOR NURSES

Structure 25mm thick medium density fiber/ particle board faced with 0.8 mm thick laminate and all the exposed edges provided with machine pressed 0.8mm thick PVC edge bands glued with hot melt EVA glue. All the panels are inter connected and attached to top with rastex, dowel and sockets (of Hettich make). All the exposed edges of under structure provided with machine pressed 0.8mm thick PVC edge bands glued with hot melt EVA glue.



STEEL CUP-BOARD

Material (Steel) with Good storage space
Option for multi drawers and lockers
Width: 1349mm
Length: 507mm
Depth: 1950mm
Each cupboard will have shelf supports on four brackets of 1.2 ± 0.10 mm thick MS Sheet. Shelves should be adjustable for height. Door panels, side & back panels shall be made out of 1.2 ± 0.10 mm M.S. thick sheet and shelves out of 1.2 ± 0.10 mm thick M.S. sheet.
Minimum thickness of pedestal CRCA MS sheet should be 1.0 mm. Sheet must be conforming to IS-513/1994. Cabinet should be fitted with 3 way bolting device and with six precision cut ISI Mark –Brass Heavy duty lever lock conforming to IS 729/79 (Reaffirmed 2001) with chrome plated handle conforming to IS 742/1981 (is must). Prior to painting the cabinet should be given phosphate treatment as per IS-3618/66 followed by as coat of red oxide primer. The lock should be as per IS and key should not be interchangeable. Test certificates are required to be produced for all the materials.



PATIENTS WAITING CHAIRS (MOULDED) SPECIFICATIONS

The unit intended for use in various location of the Emergency Department to use as waiting area chairs.

- The unit shall be a mid back chair.
- The unit should have complete steel.
- The unit should have supporting steel beam.
- The unit should black steel leg.
- The unit should have two (2) in a row.
- The unit should have three (3) in a row.
- The unit should have four (4) in a row.
- The unit should have five (5) in a row.
- The size of unit seat shall be approximately 480mm (H) x 570mm (W).
- The length of the unit shall be as follow:
 - Two (2) seater – 930mm
 - Three (3) seater – 1400mm
 - Four (4) seater – 1900mm
 - Five (5) seater – 2350mm
- The each seat length shall be approximately 450mm.
- The spacing between each seat shall be approximately 25mm.
- The frame structure shall be constructed with durable steel able to resist to rust. All joints shall be welded and all exposed surfaces shall be straight and true to line and curve. The entire structure shall be coated with a layer of anti-corrosion paint follow by another 2 finishing coats either power coating or nylon polyester coating to withstand periodic cleaning and typical abuse.
- The unit should be heavy duty.
- The unit also must be sturdy and would not sink once sit upon.
- Chair Seat Height (H): 480mm
- Chair Seat Width (W): 570mm
- Chair Seat Length (L): 450mm
- Spacing between each seat: 25mm.
- The chair shall be conductive and of good quality that are resistant to rust and typical abuse.

Sample:-



STORE ALMIRAH (STEEL)

- Steel almirah size 1980mm (H) x900mm (W) x480mm (D) manufactured from 22 gauge for body and 20 gauge for doors.
- The Almirah should have four shelves making five compartments of standard size.
- The doors of almirah provided with stiffeners made of MS sheet spot welded to the doors.
- The almirah equipped with a special three way bolting device with tongue-in groove inter locking mechanism with Three lever lock.
- The handle made from a non ferrous metal alloy, chrome plated.
- The complete almirah duly painted with synthetic enamel paint of approved shade in and outside.
- Almirah's are to be fabricated from Prime quality CRCA MS steel fully welded construction for integrity & ruggedness.
- Alimirahs are to be painted with Enamel shoving paint.

Sample:-



LED TV SPECIFICATION

Features:	Magic Remote Compatible, Time Machine, Wi-Fi Built In
Power Supply:	50-60Hz, AC 100-240V Hz
Display Features:	Full HD Features
Functionality:	Gaming TV Units
Warranty:	1
Display Type:	LED
Screen Size:	36/38/40 Inches OR more
Connectivity:	USB, WiFi
Resolution:	HD 1920x1080
Number of selectable Picture Modes:	8
Selectable Sound Modes:	6
Number of Speakers:	2
Audio Output:	20 Watts
Color:	Black
Energy Efficiency Class	A
Standby Power Consumption	300 mW
Energy Consumption per Year	85 kWh
Maximum Resolution	1920 x 1080
Operating Power Consumption	58 W
Smart TV	No
In the Box	1 TV Unit, Remote Controller, Batteries, Remote Control Batteries, Mini Wall Mount Support, Vesa Wall Mount Support, User Manual, Power Cable

LCD PROJECTOR SPECIFICATION

Display Type:	LCD
Light Output:	2500 TO 3200 Lumens
Warranty:	2 Year(s)
Features:	Digital Keystone Correction, HDMI Input, Speakers
Audio:	Mono
Life of Lamp - Full Usage:	UPTO 3000 Hours
Life of Lamp - Standard Usage:	UPTO 5000 Hours
Life of Lamp - Eco Usage:	UPTO 7000 Hours
Screen Coverage:	30 to 300 Inches
Contrast Ratio:	2500:1
Throw Ratio:	1.37 to 1.80:1
Aspect Ratio:	4:3
Brightness:	3300lm with HDMI Por
Resolution:	1080p Full HD
Audio Output:	1 Watts
Projector Lens:	1.3xManual Zoom/Manual Focus
Product Dimensions	30.2 x 23.7 x 8.2 cm
Hardware Interface	Composite Video, USB 2.0
Includes Remote	Yes

PROJECTOR SCREEN SPECIFICATION

Type:	Projector Screens Comes With 1080 P 3D And 4K Ready Technology, Black Coated Fabric From Back Side, Easy To Use And Low Maintenance, 8 Feet (Width) X 6 Feet (Height).
Resolution:	1920 x 1080 Keeps Your Eyes Strain Free While Viewing, Comes With Anti Uv Coating To Protect Eyes, A+++++ Grade Fabric, Ideal For Presentations, Meeting Rooms, Home Cinema
Size:	5 Ft.(H) x 7 Ft (W) / 8 Ft.(W) x 6 Ft(H)
Purpose:	Ideal For Presentation, Meetings Rooms, Home Cinema
Compatible Devices	Compatible With all the Projectors Available in the Market, Comes With 1080 P 3D and 4K Ready Technology
Additional Features	Comes With Metal Tripod Stand, Supports 3 D and Full HDTV Format

EXTERNAL HARD DISK SPECIFICATION

<p>Drag and drop file saving, right out of the box</p> <p>USB powered</p> <p>Fast data transfer with USB 2.0 or more connectivity</p>	<p>Simply plug the included USB cable into your computer – no external power supply is needed.</p> <p>The drive is automatically recognised by the Windows operating system – no software to install and nothing to configure.</p> <p>Drag and drop to save files to the Expansion portable drive.</p> <p>Built-in power management automatically ensures energy-efficient operation</p>
Capacity	500 GB/ 1TB/ 2TB/ 3TB
Weight	2.25 lbs
Type	power adapter
Storage Interface	USB 2.0 or more
Interface	USB 2.0 or more
Interface Transfer Rate	480 Mbps
Spindle Speed	7200 rpm
Form Factor	3.5"
Interface Type	USB 2.0 or more
Hard Drive Type	external hard drive
External Drive Type	desktop
Form Factor (Short)	3.5"
Form Factor (metric)	8.9 cm
Form Factor (Short) (metric)	8.9 cm
OS Required	Apple MacOS X 10.4.8 or later, Microsoft Windows Vista / XP
Power Source	included AC adapter
Interface Speed	480 Mbps
Type	2 years warranty

DVD PLAYER SPECIFICATION

D/A converter	12 bit, 108 MHz
Picture enhancement	Progressive scan
	Video up sampling
Playback Media	CD
	CD-R/CD-RW
	Video CD/SVCD
	DVD
	DVD+R/+RW
	DVD-R/-RW
	DVD-Video
Compression formats	MPEG1
	MPEG2
Video disc playback system	PAL
	NTSC
Playback Media	DVD+R/+RW
	DVD-R/-RW
	CD-R/RW
	Picture CD
	Kodak Picture CD
Picture Compression Format	JPEG
Picture Enhancement	Flip photos
	Rotate
	Zoom
	Slideshow
	Slideshow with MP3 playback
Child Protection	Child Lock
	Parental Control
On-Screen Display languages	English
SOUND	
D/A converter	24 bit, 192 kHz
Frequency response	30-20000 Hz
Signal to noise ratio	> 90
Distortion and Noise (1kHz)	> 65 dB
Crosstalk (1kHz)	> 70 dB
Dynamic Range (1kHz)	> 80 dB
Sound System	Dolby Digital
Playback Media	CD
	MP3-CD
	MP3-DVD
	WMA-CD
	CD-R/RW
	Audio CD

Compression format	MP3
	Dolby Digital
	PCM
	WMA
MP3 bit rates	32 - 320 kbps
Multimedia connections	USB memory class device
Playback Formats	JPEG Still pictures
	MP3
Rear Connections	Composite video (CVBS) output
	Component Video out Progressive
	Analog audio Multi-channel out
Front / Side connections	USB
Power supply	110-240V
	50/60 Hz
Power consumption	< 10 W
Standby power consumption	< 1W
Included accessories	Audio/Video cable
	Remote Control
	World Wide Warranty leaflet
	Quick start guide

WHITE/COLOUR BOARDS SPECIFICATION

White Board non magnetic deluxe series is a premium quality white board comes with triple layer high pressure melamine coated surface for smooth writing and erasing and for extra long life of the surface.

CONTENTS OF THE PACK:

The pack comes with a white board marker, duster,

APPLICATION: The board is ideal for use in Office & Conference rooms

- Home & Home office
- Schools & College classrooms
- Training rooms
- Showrooms for writing messages

FEATURES:

- Rounded corners and elegant frame for good aesthetics
- Clips for hanging at four sides, hanging can be done in both landscape & portrait
- Triple layer coated surface for smooth writing & erasing Disclaimer: The design of corner or colour may vary due to continuous product development, the brand shown of marker shall vary than original, marker image is indicative.
 - Whiteboard Height: 45 mm
 - Whiteboard Width: 60 mm

ABC TYPE FIRE EXTINGUISHER SPECIFICATION

- SO & CE Certified
- Helium Leak Tested, 5 years Warranty
- Clear Instruction Label
- Useful for Home, Office, Buildings, Warehouses etc.
- Fire Rating 2A,21B

Fire extinguisher 4kg (multipurpose fire extinguisher) dry powder stored pressure type technical specification –

Contents: abc dry powder operating : -10 to +55 c°

Capacity: 4kg service

Pressure: 15 bar

Gross weight: 6.65 kgs.

Tested at: 35 kgf/cm² fire

Rating : 2a & 21b

Maintenance: - care and maintenance as per is 2190 : 2010 inspect periodically and ensure that there is no pressure drop. Lock pin and wire seal must be intact.

Inspection: - the seal and temper indicator are not broken or missing it is full (by weighing or lifting) it is not obviously damage, corroded, leaking or has clogged nozzle. Its pressure gauge reading and indicator is the operable range or position.

Precaution: - contents under pressure. Do not temper with the shell. Break the safety seal only in case of fire. Do not relay on partially used or discharge extinguisher. Recharge immediately after use.

MEETING HALL CHAIRS

Sample:-



The unit intended for use in meeting hall/ Conference hall.

- The unit shall have pure Steel.
- The unit should be in black colour.
- The size of unit shall be approximately 600mm in diameters
- The unit shall come with an armrest.
- The frame structure shall be constructed with durable steel able to resist rusting. All joints shall be welded and all exposed surfaces shall be straight and true to line and curve.
- The unit should be heavy duty.
- The unit also must be sturdy and would not sink once sit upon.

- The backrest should conform to the natural curvature of your spine, and provide adequate lumbar support.
- The safe loading capacity of the seat shall be approximately about 100 kg excluding the weight of unit itself.

Optional Accessories

All optional accessories or consumables that are optional shall be listed separately with unit prices clearly indicated.

INTEL CORE I5 LAPTOP SPECIFICATION

Item	Item Details / Description /Specification
Constructions and Externals	Metal/Alloy/reinforced hinges for display. The Casing ABS plastic
Processors	Intel i5 7th Generation processor / equivalent AMD processor with minimum 2 core, 2.5 GHz frequency or higher and 3 MB Cache or higher
Chipset	OEM Chipset Motherboard
Wireless	Integrated wireless 802.11 b/g/n with Bluetooth 4.0
Memory	8 GB DDR4 SDRAM (2133 MHz) or higher
Hard Disk Drive	1 TB SATA or higher with 5400 rpm
Graphics	Integrated HD Graphics
Display	Not more than 15.6-inch diagonal LED- backlit (1366 x 768 resolution)
Audio	Integrated HD Audio
Optical Drive	Internal DVD RW
Webcam	720p HD webcam
Wireless & Bluetooth	Wifi 802.11 b/g/n and Bluetooth 4.0 or higher
Keyboard	Spill –resistant keyboard with Touchpad
Ethernet Interface	Integrated Gigabit Ethernet 10/100/1000
Ports	1 X USB Type – C (Inbuilt or through External Adapter)
	2 X USB 3.0
	1 X VGA
	1 X HDMI
	1 X Headphone / microphone Combo
	1 X Power connector
	1 X Ethernet
1 X Inbuilt MMC Card Reader	
Integrated Media Card Reader	multi-format digital media reader
Weight	not more than 2.5 Kgs with battery
Security	Integrated Fingerprint Reader, TPM 2.0
Speaker & Microphones	Integrated stereo speakers & Integrated microphone
Trusted Platform Enabled	Yes
Battery	Internal 40 WHr battery with minimum 5 Hours of battery back-up time
Operating System	Preloaded Genuine Windows 10 Professional 64

	bit.
Anti-Virus	Antivirus with Antimalware and Internet security with 5 years Subscription.
Certification	Energy Star®/BEE Version I, RoHS, Windows and Linux Compliance Certificate.
AC Power Adapter	Input Voltage Range 100V- 240V, 50 Hz AC power adapter with necessary cables
OEM/Product Certification	ISO 9001:2015, Energy Star 6.1 or TCO, ISO 14001:2015 or EPEAT India Certification, FCC or CE, RoHS, Windows, Linux
Standard Accessories	Power cable, Power Adaptor and Charger, User Manuals and Laptop backpack carry bags
Warranty	5 Years Onsite OEM warranty (OEM undertaking on letter head need to be submitted along with bid) excluding battery

PHOTO COPIER MACHINE SPECIFICATION

Print / Copy / Scan		
Type	B / W Laser Multifunctional (Reader / Printer Console)	
Maximum Original Size	A3	
Fixing System	On-demand Fusing	
Copy Speed	A4	20ppm
	A3	10ppm
First Copy Time	7.9secs	
Warm-Up Time	From Power On	13secs
	From Sleep Mode	2.9secs (The time it takes from recovery sleep to the start key is enabled)
Print Description Language	UFR II Lite	
OS compatibility	Windows 8.1 / 8 / 7 / Vista / XP / 2000, Windows Server 2012 / Server 2008 / Server 2003, Mac OS X 10.5.8 or later	
Resolution	Scan	300 x 300dpi
	Copy	600 x 600dpi
	Print	600 x 600dpi
Pull Scan (MF Toolbox / Scangear)	B / W & Color	
Push Scan (MF Toolbox)	B / W & Color	
Scan Features	TWAIN, WIA compatible	
Supported File Format (Scan)	PDF / Searchable PDF / Compact PDF, BMP, JPEG, TIFF	
Processor speed	400MHZ	
Memory Capacity	128MB	
Paper handling		
Paper Sizes	Cassette 1	A3, B4, A4R, A4, B5R, B5, A5R
	Cassette 2 (Optional)	A3, B4, A4R, A4, B5R, B5, A5R

	Bypass Tray	A3, B4, A4R, A4, B5R, B5, A5R, Envelope (COM 10, Monarch, ISO-C5, DL)
Acceptable Originals	Sheet, Book, and Three dimensional objects (up to 2kg)	
Available Paper	Drawer	Weight: 64 to 90gsm Type: Plain, Recycled, Color (64 to 80gsm), Bond (75 to 90gsm)
	Bypass Tray	Weight: 64 to 128gsm Type: Plain, Recycled, Color (64 to 80gsm), Bond (75 to 90gsm), Heavy Paper 1 (91 to 105gsm), Heavy Paper 2 (106 to 128gsm), Transparencies, Labels, Envelopes
Paper Capacity	Cassette 1	250 sheets (80gsm)
	Cassette 2 (Optional)	250 sheets (80gsm)
	Bypass Tray	80 sheets (80gsm)
Connectivity		
Interface	Network	Ethernet 100BASE-TX / 10BASE-T
	Others	USB 1.1 / 2.0
Network Protocol	TCP/IP v4/v6	
General Specifications		
Power Consumption	Sleep	2.0W or less
	Maximum	1.5kW or less
Power Supply	220 - 240V AC, 50 / 60Hz	
Toner Yield	Approx. 10,200 sheets (A4, 6% coverage)	
Drum Yield	Approx. 61,700 sheets	
Dimensions (W x D x H)	622 x 589 x 607mm (with ADF)	
Weight	Approx. 35.5kg (with ADF)	
Installation Space (W x D)	921 x 589mm (when the Bypass Tray is extended)	
Department ID Management	Up to 100 departments	
Optional Accessories		
Duplex Automatic Document Feeder - AM1		
Type	Automatic Document Feeder	
Size of Originals	A3, B4, A4, A4R, B5, B5R, A5, A5R	
Paper Weight	When continuously scanning originals: 52 to 105gsm When scanning a single original: 37 to 128gsm	
Max. Number of Originals	50 sheets (80gsm)	
Scanning Speed (Max)	Copying (A4 in Black-and-White at 600dpi)	1-sided scanning: 20ipm 2-sided scanning: 8ipm
	Scanning	1-sided scanning:

		23.4ipm (A4 in B / W at 300dpi) 12ipm (A4 in Color at 300dpi) 2-sided scanning: 8ipm (A4 in B / W at 300dpi) 4ipm (A4 in Color at 300dpi)
Dimensions (W x D x H)	565 x 520.5 x 126mm	
Weight	7.0kg	
Cassette Unit - AB1		
Paper Sizes	A3, B4, A4, A4-R, B5, B5-R, A5-R	
Paper Capacity	250 sheets (80gsm)	
Power Source	From main unit	
Dimensions (W x D x H)	579 x 575 x 116mm	
Weight	Approx. 5.75kg	
Other Optional Accessories	Duplex Unit-C1, Platen Cover Type T, FL Cassette-AU1, Heater Kit-M1, Cassette Heater Unit-30, iR Pedestal Type M	

HEAVY DUTY SCANNER SPECIFICATION

Type	Duplex
Element Type	CCD
Light Source	Light Emitting Diode (LED)
Scanning Speed	Up to 45 ppm/90 ipm (black-and-white, grayscale, color, both 200 dpi and 300 dpi)
Color Depth	48 bit
Optical Resolution	Up to 600 dpi
Interpolated Resolution	Up to 600 x 600 dpi
Max. Document Size	8.5" x 122"
Media Type	Paper (plain, inkjet), envelopes, labels, cards (business, insurance, embossed, plastic ID, credit)
Automatic Document Feeder (ADF)	Yes
USB Ports	Yes
Power Requirements	AC 100 - 240V, 50 / 60 Hz
Power Consumption	8.5 watts (Ready), 1.822 watts (Sleep), 0.203 watts (Auto-Off)
Operating Systems Supported	Microsoft Windows 7 (32-bit, 64-bit), Windows Vista (32-bit, 64-bit), Windows XP, service pack 3
Features	<p>Productive and reliable document capture</p> <ul style="list-style-type: none"> - Quickly and easily scan each and every page with confidence - Quickly scan up to 45 ppm and 90 ipm in black-and-white, grayscale, and color. - Improve productivity with a robust and reliable 3000-page duty cycle.

	<ul style="list-style-type: none"> - Get worry-free, consistent, high-quality images Easy-to-integrate workflow solutions - Create profiles for frequent, common jobs and scan directly to a variety of destinations and applications. - Automatically improve the accuracy of scanned images with included Kofax Virtual ReScan Pro software. - Convert scans into editable text with IRIS Readiris Pro OCR, and save scans as multiple file types. - Seamlessly integrate the scanner into existing systems with industry-standard drivers. <p>Space- and energy-saving design</p> <ul style="list-style-type: none"> - Keep more of your workspace for yourself. A smaller footprint lets you locate the scanner where convenient. - Help increase your energy efficiency as well as your productivity, thanks to the ENERGY STAR rating. - Take pride in using a scanner with an EPEAT Silver certification. - help you conserve resources with recyclable packaging.
--	---

FLATBED SCANNER SPECIFICATION

Name	Description
Scanner type	Flatbed Flatbed with transparent materials adapter (TMA)
Size	280 x 486.5 x 52 mm (11.0 x 19.1 x 2.0inches) 287 x 450 x 59 mm (11.3 x 17.72 x 2.32 inches)
Weight	1.7kg (3.74 lbs) 3.1 kg (6.8 lbs.)
Scanning element	Charged-coupled device
Interface	USB 1.0 USB 2.0 Hi-Speed
Hardware resolution	1200 x 1200 dpi hardware resolution 2400 x 4800 dpi hardware resolution
Selectable resolution	12 dpi to 999,999 enhanced dpi at 100 percent scaling
AC line voltage	100-120 V 60 Hz – North America 200-240 V 50 Hz – Continental Europe, United Kingdom, Australia 100-240 V 50 Hz/60 Hz – Rest of the world

BMW M ITEMS







Installation / Commissioning Requirements

- The unit shall be fully assembled in the Bidder's factory before delivery to site for commissioning. The Bidder shall arrange with the Hospital, Materials Management Department representative for delivery. During the commissioning, the Bidder shall carry out the necessary functional tests in accordance to the manufacturer's recommendation. The Bidder shall provide all necessary testing equipment or required for the functional testes at their own expenses. No claim for extra payment will be entertained by the Hospital owing to the Bidder's neglect any unforeseen difficulties for which provision are not made for the commissioning. A Bidder, by the fact of submission of tender, shall be deemed to have accepted all conditions and stipulations of this clause, which shall be binding on the Bidder.

Additional Requirements (where applicable)

- The supplied equipment and accessories must be of hospital-grade and shall comply with national and international recognised Standards and applicable Standard Systems.
- The Tenderer shall provide back-up units during the warranty period while the unit is undergoing corrective repair by the Tenderer.
- The warranty shall cover unlimited breakdown service calls at no additional cost.
- The Tenderer is advice to check for incompleteness and misleading information that may result in disqualification.

- All terms and conditions which are printed on or referenced in the successful Tenderer's Bill of Sale or other sales documentation for the equipment to be purchased are null and void and are not binding to the Company. The Company will dictate all terms and conditions of the sale.
- The Company will be entitled to purchase all replacement parts, components, sub-assemblies and peripheral devices as needed for the maintenance and repair of each model of equipment purchased from the successful Tenderer at the fair market price. No excessive handling or shipping charges will be applied to these purchases. The successful Tenderer must expedite all shipments and not withhold shipments in order to increase equipment downtime to the Company or for any other reasons.
- The Company has the right to use any service representative of his choosing, including in-house, third party or independent contractor. These representatives have the right to repair, install, calibrate, maintain or overhaul all models of equipment purchased from the successful Tenderer. The Company's representatives shall be afforded the privilege of ordering all necessary repair parts and components from the successful Tenderer for each model of equipment purchased at a fair market price.
- The Company has the right to send its designated service representatives to the manufacturer's service training school to receive sufficient, any or all, technical training to allow the representative to repair and calibrate the equipment purchased.
- The Tenderer is advised to check for incompleteness and misleading information that may result in disqualification.
- Failure to comply with any of the above requirements may result in the rejection of the offer.

CHECK LIST

(To be submitted in **Technical Bid**)

Note : The documents has to be arranged serially as per the order mentioned in the check list

Please put ✓ in the respective box

COVER – A (TECHNICAL BID)

DOCUMENTS: SUBMITTED OR NOT

1.	List of Item (s)	Page No	Yes	No
2.	Tender document Fee	Page No	Yes	No
3.	Earnest Money Deposit	Page No.	Yes	No
4.	Declaration form signed by the Tenderer & affidavit before Notary Public / Executive Magistrate	Page No.	Yes	No
5.	Manufacturer's original Authorization	Page No.	Yes	No
6.	Deviation/No deviation Statement (Item wise) & details of technical specification	Page No	Yes	No
7.	Copy of Valid ISO Certificate	Page No	Yes	No
8.	Photocopy of PAN	Page No.	Yes	No
9.	Photocopy of monthly GST return certificate And GST Certificate copy	Page No	Yes	No
10.	Copy of original Tender and schedules, duly Signed by the Tenderer	Page No.	Yes	No.

(To be submitted in **Part A -Technical Bid**)

STATEMENT REGARDING DEVIATIONS FROM TECHNICAL SPECIFICATIONS (IF ANY)

Following are the Technical deviations and variations from the purchaser's Technical Specifications.

Sl. No.	Item Name	Clause of Technical Specification	Statement of Deviations / Variations
1			
2			
..			
..			
..			

In case there is no deviation from technical specification, Pl. Mention *No Deviation*.

Signature of the Bidder

Name:

Date:

Place:

Seal

(To be submitted in **Cover -Technical Bid**)
DECLARATION FORM/ AFFIDAVIT

I / Wehaving My /
our.....office at.....do declare that
I / We have carefully read all the terms & conditions of tender of the _____, Orissa
for the supply of Equipment, Instrument & furnitures for Gajapati District. The approved rate will
remain valid for a period of one year from the date of approval. I will abide with **all the terms &**
conditions set forth in the **Tender Reference**
no._____.

I/We do hereby declare I/We have not been de-recognized / black listed by any State
Govt. / Union Territory / Govt. of India / Govt. Organization / Govt. Health Institutions for supply
of Not of Standard Quality (NSQ) items / non-supply.

I/We agree that the Tender Inviting Authority can forfeit the Earnest Money Deposit and
blacklist me/us for a period of 3 years if, any information furnished by us proved to be false at
the time of inspection / verification and not complying with the Tender terms & conditions.

Seal

Signature of the bidder:
Date:
Name & Address of the Firm:

Affidavit before Executive Magistrate / Notary Public.

PART B - PRICE BID FORMAT

SL No	Name of the Item	Specification	Name of the Manufacturer	Unit Price	GST	Total price	Warranty period

Yours Sincerely,

CDM & PHO, Gajapati

[Handwritten signature]
10-5-18